

**QDPP&E**



QUALITY DISCOUNT PRESS PARTS & EQUIPMENT + AAA PRESS INTERNATIONAL

**ERHARDT+LEIMER**

**2022**

WEB Guides



## DR2280 Mark Andy Retrofit

Used for retrofit to MA2200 or MA4150.  
 10" WEB WIDTH W/ DR2280 300 MM ROLL FACE  
 BY 300 SPAN, 60 MM DIA ROLLS FX4631 SENSOR.  
 DC1340 CONTROLLER WITH POWER SUPPLY  
 W/ MOUNTING PLATE KBS9950 FOR 14.5"  
 BETWEEN FRAMES CAN 2.0, 110V AC, 2-E1-A1-B-  
 LR



## Rotoflex Retrofit

New Digital controls to replace the old analog controls  
 on a Rotoflex Rewinder. The new AG2491 should  
 bold in place of the old AG0491 actuator.  
 CONTROL SYSTEM TO RETROFIT AROTOFLEX  
 WEB GUIDER  
 CONSISTING OF:  
 ACTUATOR AG2491 +-12 MM STROKE  
 CONTROLLER DC1340 WITH OPERATOR PANEL  
 SENSOR FX4631 ULTRASONIC WITH 270 MM  
 CABLE WITH PLUG  
 SENSOR CABLE SPIRAL 0.7 TO 2.8 M LONG WITH  
 PLUG  
 RETURN TO CENTER PROXIMITY SENSOR  
 BRACKET FOR PROX SENSOR  
 LAYOUT CONFIGURATION 2-A-II-RL  
 POWER SUPPLY 24V DC 5 A, 110-220 AC INPUT



## Arpeco Tracker Retrofit

ACTUATOR AG9111 +- 50MM STROKE, 1000N, 30  
 MM/SEC WITH BRUSH-LESS DIRECT DRIVE &  
 INTERGRATED CONTROLLER  
 CLEVIS MOUNTING BRACKET FOR AG 9...  
 ACTUTAOORS  
 DO3001 COMMAND STATION FOR ACTUATOR  
 AG9...,  
 MOUNTING PER DWG M 158446, 24V DC, 10A  
 MOUNTING BRACKET / BASE FOR DO3001  
 OPERATOR PANEL  
 CABLE 3M LONG, CONNECTORS M12 MS / M12  
 FS, 4-POLE, A CODE, IP67  
 AG9 TO DO3  
 ETHERNET CABLE 3 M LONG, CONNECTORS  
 M8X1, 4-POLE, A CODE, IP67  
 FE5201 TO DO4021, OR AG9 TO DO3  
 CABLE M8 MALE/ M16 FEM PLUG 6 PIN, SENSOR  
 EXTENSION ADDAPTOR  
 DO3001 TO M16 SENSOR SOCKET, 3 M LONG  
 SENSOR ULTRASONIC FX5230, 30MM GAP, +/-  
 10MM RANGE, CAN 1&2  
 CAB ASSY 1.00 SQ BAR W/BRKT FOR  
 FX4230/FX5230

**TECHNICAL PROPOSAL**

**DATE:** 2022  
**PROPOSAL:** 20383877  
**SHIPMENT:** 8 Weeks

**APPLICATION SUMMARY: CONTROL SYSTEM RETROFIT FOR WEBTRON PRESS**

| <b>ITEM NO.</b> | <b>QTY.</b> | <b>DESCRIPTION</b>  |
|-----------------|-------------|---|
| 1.              | 1           | Webtron Retrofit kit consisting of: <ul style="list-style-type: none"><li>• AG9101 ACTUATOR +- 25MM STROKE</li><li>• DO3301 OPERATOR PANEL</li><li>• FX4631 EDGE SENSOR</li><li>• SENSOR MOUNTING BLOCK</li><li>• CABLES 5 M LONG</li><li>• 24V DC 10 A</li><li>• CONFIG: 1-A-II-LR</li></ul> |
| 2.              | 1           | Operating instruction manual in English   |



QUALITY DISCOUNT PRESS PARTS & EQUIPMENT + AAA PRESS INTERNATIONAL

## TECHNICAL PROPOSAL

### **NOTES:**

1. Customer to install system and connect electrically
2. E+L to provide complete instructions for installation, operation and maintenance with shipment.

### **TERMS:**

1. Payment terms subject to credit approval.
2. F.O.B. Duncan, SC without installation, special packaging or handling.
3. This proposal is valid for 90 days from above date.
4. Above delivery schedule subject to final engineering approval.

2022

Load cell kits

PD-2125 with adaptor kit

20 times over load, nickel coated

(2) 457277 PD-2125 Load Cell 0.15Kn (33 LB)

OR

(2) 457279 PD-2125 Load Cell 0.3Kn (67 LB)

OR

(2) 457281 PD-2125 Load Cell 0.75Kn (168 LB)

(2) 45449 5 Meter cables

(1) set 67096 bearing kit

(2) 514958 Back Plate center mount for PD2125

Clamp adaptor for live or dead shaft journal

(2) 514955 Clamp for 0.75-inch journal dia.

OR

(2) 514956 Clamp for 1.0-inch journal dia.

OR

(2) 514957 Clamp for 1.25-inch journal dia.

(1) DC6201 digital web tension controller, with enclosure. M12 D-coded interface: Ethernet/IP, Ethernet/UDP

